Ariterm CONSTRUCTION HEAT

ARITERM ENERGY

Ariterm Construction Heat system is a heat center that can be easily moved and quickly put into use. It produces carbon-neutral warm air or hot water with renewable fuel.

Construction Heat system is designed especially for the needs of the construction industry or for the production of temporary heat.

The system consists of two portable containers. The lower container has the heating center itself and the upper one has the fuel storage.

Power kW	200	300	400	500
Measures, mm (P x L x H)	6000 x 2500 x 6000			
Weight, kg. Container 1 and 2. Empty	8000 and 4000	9000 and 4000	10000 and 4000	11000 and 4000
Weight, kg. Container 1 and 2. In use	10000 and 20000	11000 and 20000	12500 and 20000	14000 and 20000
Pellet storage size, gross m^3	25	25	25	25
Operating voltage, V	400	400	400	400
Main fuse, A	3 x 35	3 x 35	3 x 35	3 x 35
Heat exchanger for the heating circuit	1	1	1	1
Heating circuit pump	1	1	1	1
Pump output				7 l/s, 200kPa
Connection	Camlock 2"	Camlock 2"	Camlock 2"	Camlock 2"
Energy meter	1	1	1	1

Hot water 200 – 500 kW

The container that produces hot water is suitable for large and labyrinthine spaces. The container can be connected to an existing system or hot water fans. The container is equipped with a heating boiler and burner manufactured by Ariterm Energy Oy.




Risto Mikkonen +358 44 533 7787 risto.mikkonen@aritermenergy.fi

Clean heat for the construction site from nature












www.ariterm.fi



Standard equipment

- Burner
- Boiler
- Automatic cleaning
- Fuel feeding
- Automation, sensors
- Flue gas cleaner and fan
- Chimney, modular construction
- Circulation pump
- Heat exchanger
- Boiler circuit pump
- Energy meter
- Remote connectionText message alert

In our product range, there is a suitable solution for objects that require different heating power.

The devices adjust automatically when the heat demand changes and work reliably even with lower partial outputs.

